

UVEMI NEO60

For disinfection of air.

SPECIFICATIONS

Manufacturer	Bioclimatic B.V.
In accordance with	CE (2014/35/EU, 2014/30/EU, 2011/65/EU)
IP Rating	IP51
Supply voltage [VAC]	220 - 240 (50 / 60 Hz)
Material	AISI 304, powder coated white
RAL colour	RAL 9016
Operating temperature [°C]	10 - 40
UVC tube type	6030(D)(T) (2x29 W)
Power consumption [W]	70
Weight [kg]	12
Treated air flow rate [m3/h]	225
Lifespan of UVC tube [hours]	12000
Noise production [dB]	42
Power cable length [m]	1,5

TECHNICAL CHANGES RESERVED

The **UVEMI NEO60** is designed to provide effective air disinfection in small to medium-sized spaces. The unit is suitable for applications such as laboratories, waiting rooms and office environments, where maintaining a hygienic indoor environment is essential. Its compact design allows for easy placement in a wide range of indoor environments, delivering reliable reduction of airborne viruses, bacteria and mold.



Disinfection with the UVEMI NEO60

- ✓ Flexible and efficient
- ✓ Standalone for use in laboratories, waiting rooms, office environments
- ✓ Helps prevent spreading of viruses and bacteria

TECHNICAL INFORMATION

UVEMI NEO60

Lamp	Quantity
6030(D)(T)	2x

